

Cable mm ²	Stud Hole E	Australian Standard Cable Terminal Ends Dimensions						
		A	D	F	B	G	H	J
1.5 – 4	4.2	2	8	1	7.5	4	5	18.5
1.5 – 5	5.2	2	8	1	7.5	4	5	18.5
1.5 – 6	6.5	2	10	0.8	7.5	4	6	19.5
2.5 – 4	4.2	2.5	8	1	8	4	5	19
2.5 – 5	5.2	2.5	10	0.8	8	5	6	20
2.5 – 6	6.5	2.5	10	0.8	8	5	6	20
2.5 – 8	8.4	2.5	11	0.7	8	6	9	26
4 – 5	5.2	3.3	10	1	9	5	6	22
4 – 6	6.5	3.3	10	1	9	5	6	22
4 – 8	8.4	3.3	12	0.8	9	6	9	26
4 – 10	10.2	3.3	15	0.8	9	8	11	32
6 – 5	5.2	3.8	10	1.2	10	5	6	23
6 – 6	6.5	3.8	12	1	10	6	9	27
6 – 8	8.4	3.8	12	1	10	6	9	27
6 – 10	10.2	3.8	15	0.8	10	8	11	32

10 - 5	5.2	4.7	12	1.8	10	6	7	27
10 - 6	6.5	4.7	12	1.8	10	6	7	27
10 - 8	8.4	4.7	14	1.6	10	7	8	29
10 - 10	10.5	4.7	15	1.5	10	8	10	32
10 - 12	13	4.7	18	1	10	10	12	38
16 - 6	6.5	5.5	11	2.4	19	7	9	39
16 - 8	8.4	5.5	14	1.7	19	7	9	39
16 - 10	10.5	5.5	16	1.5	19	8	10	41
16 - 12	13	5.5	18	1.2	19	10	13	46
25 - 6	6.5	7.1	13.5	2.4	21	7	9	41
25 - 8	8.4	7.1	13.5	2.4	21	7	9	41
25 - 10	10.5	7.1	16	1.9	21	9	10	44
25 - 12	13	7.1	18	1.6	21	10	13	48
35 - 6	6.5	8.4	16	3	21	9	10	45
35 - 8	8.4	8.4	16	3	21	9	10	45
35 - 10	10.5	8.4	18	2.6	21	9	10	45
35 - 12	13	8.4	20	2.2	22	11	13	51
50 - 6	6.5	9.5	18	3.3	22	8	10	46
50 - 8	8.4	9.5	18	3.3	22	8	10	46
50 - 10	10.5	9.5	18	3.3	22	8	10	52
50 - 12	13	9.5	21	2.7	22	11	13	54
70 - 6	6.5	11.3	21	3.5	22	11	13	54
70 - 8	8.4	11.3	21	3.5	24	11	13	54
70 - 10	10.5	11.3	21	3.5	24	11	13	54

70 – 10	10.5	11.3	21	3.5	24	11	13	54
70 – 12	13	11.3	21	3.5	24	11	13	54
70 – 16	17	11.3	26	3	24	14	60	61
95 – 8	8.4	13.5	25	4	27	12	14	60
95 – 10	10.5	13.5	25	4	27	12	14	60
95 – 12	13	13.5	25	4	27	12	14	60
95 – 16	17	13.5	25	3.5	27	14	16	61
120 – 8	8.4	15.6	30	5	30	12	14	64
120 – 10	10.5	15.6	30	5	30	12	14	64
120 – 12	13	15.6	30	5	30	12	14	64
120 – 16	17	15.6	30	5	30	16	16	72
150 – 10	10.5	16.7	32	5.8	30	16	16	71
150 – 12	13	16.7	32	5.8	32	18	18	75
150 – 16	17	16.7	32	5.8	30	18	18	75
185 – 10	18.4	10.5	36	5.8	32	16	16	74
185 – 12	13	18.5	36	5.8	32	18	18	79
185 – 16	17	18.4	36	5.8	32	18	18	79
240 – BL	-	21.2	41	7	38	21	21	92
240 – 10	10.5	21.2	41	7	38	21	21	92
240 – 12	13	21.2	41	7	38	21	21	92
240 – 16	17	21.2	41	7	38	21	21	92
300 – BL	-	23.8	46	7.8	42	23	23	101
300 – 12	13	23.8	46	7.8	42	23	23	101
300 – 16	17	23.8	46	7.8	42	23	23	101
400 – BL	-	26.8	50	8	44	24	24	107
500 – BL	-	30	56	9	50	27	27	119
630 – BL	-	34	64.4	11	58	32	32	139